

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the above-identified application.

Listing of Claims

1. (Currently Amended) A method comprising:
maintaining first and second data volumes, wherein the first data volume is unrelated to
the second data volume;
~~preserving data of the second data volume; and~~
refreshing the second data volume to data of the first data volume so that the second data
volume becomes a point-in-time (PIT) copy of the first data volume, wherein
refreshing the second data volume comprises overwriting all data of the second
data volume with data copied from the first data volume;
modifying data of the first data volume before any or all data of the second data volume
is overwritten with data copied from the first data volume;
modifying data of the second data volume before any or all data of the second data
volume is overwritten with data copied from the first data volume.
2. (Cancelled)
3. (Cancelled)
4. (Original) The method of claim 1 further comprising creating one or more PIT copies of
the first data volume prior to refreshing the second data volume to the data contents of the first
data volume.
5. (Previously Presented) The method of claim 4 wherein one of the PIT copies of the first
data volume is in a virtual state when the second data volume is refreshed to the data of the first
data volume.

6. (Previously Presented) The method of claim 1 wherein said preserving comprises creating one or more PIT copies of the second data volume prior to refreshing the second data volume to the data contents of the first data volume.
7. (Previously Presented) The method of claim 6 wherein one of the PIT copies of the second data volume is in the virtual state when the second data volume is refreshed to the data of the first data volume.
8. (Previously Presented) The method of claim 1 wherein the first data volume is a real or virtual PIT copy of another data volume when the second data volume is refreshed to the data of the first data volume.
9. (Previously Presented) The method of claim 1 wherein the second data volume is a real or virtual PIT copy of another data volume when the second data volume is refreshed to the data of the first data volume.
10. (Original) The method of claim 1 wherein refreshing the second data volume further comprises generating first and second maps in memory, wherein each of the first and second maps comprises a plurality of entries, wherein each entry of the first map corresponds to a respective memory block that stores data of the first data volume, and wherein each entry of the second map corresponds to a respective memory block that stores data of the second data volume.
11. (Previously Presented) The method of claim 10 wherein refreshing the second data volume further comprises:
 - setting a first bit in each entry of the first map, wherein each first bit of the first map is set to indicate its respective memory block stores valid data; and
 - clearing a first bit in each entry of the second map, wherein each first bit of the second map is set to indicate its respective memory block stores invalid data.

12. (Original) The method of claim 11 further comprising:
setting or clearing a second bit in each entry of the second map to indicate that its
respective memory block stores data needed for a PIT copy of the second data
volume.
13. (Previously Presented) The method of claim 1 wherein said preserving comprises
creating a PIT copy of the second data volume before or while refreshing the second data volume
to the data of the first data volume.
14. (Cancelled)
15. (Currently Amended) A computer readable medium storing instructions executable by a
computer system, wherein the computer system implements a method in response to executing
the instructions, the method comprising:
~~preserving the data contents of the second volume, and~~
refreshing a second data volume to the data of a first data volume so that the second data
volume becomes a PIT copy of the first data volume, wherein refreshing the
second data volume comprises overwriting all data of the second data volume
with data copied from the first data volume, and wherein the first data volume is
unrelated to the second data volume prior to refreshing the second data volume to
the data of the first data volume;
modifying data copied to the second data volume before any or all data of the second data
volume is overwritten with data copied from the first data volume;
modifying data of the first data volume before any or all data of the second data volume
is overwritten with data copied from the first data volume.
16. (Cancelled)
17. (Cancelled)

18. (Previously Presented) The computer readable medium of claim 15 wherein the method further comprises creating one or more PIT copies of the first data volume prior to refreshing the second data volume to the data of the first data volume.

19. (Previously Presented) The computer readable medium of claim 18 wherein one of the PIT copies of the first data volume is in the virtual state when the second data volume is refreshed to the data of the first data volume.

20. (Previously Presented) The computer readable medium of claim 15 wherein said preserving further comprises creating one or more PIT copies of the second data volume prior to refreshing the second data volume to the data of the first data volume.

21. (Previously Presented) The computer readable medium of claim 20 wherein one of the PIT copies of the second data volume is in the virtual state when the second data volume is refreshed to the data of the first data volume.

22. (Previously Presented) The computer readable medium of claim 15 wherein the first data volume is a real or virtual PIT copy of another data volume when the second data volume is refreshed to the data of the first data volume.

23. (Currently Amended) The computer readable medium of claim ~~24~~ 15 wherein the second data volume is a real or virtual PIT copy of another data volume when the second data volume is refreshed to the data of the first data volume.

24. (Original) The computer readable medium of claim 15 wherein refreshing the second data volume further comprises generating first and second maps in memory, wherein each of the first and second maps comprises a plurality of entries, wherein each entry of the first map corresponds to a respective memory block that stores data of the first data volume, and wherein each entry of the second map corresponds to a respective memory block that stores data of the second data volume.

25. (Previously Presented) The computer readable medium of claim 24 wherein refreshing the second data volume further comprises:

clearing a first bit in each entry of the first map, wherein each first bit of the first map is set to indicate its respective memory block stores valid data; and
setting a first bit in each entry of the second map, wherein each first bit of the second map is set to indicate its respective memory block stores invalid data.

26. (Previously Presented) The computer readable medium of claim 15 wherein said preserving further comprises creating a PIT copy of the second data volume before or while refreshing the second data volume to the data of the first data volume.

27. (Cancelled)

28. (Cancelled)

29. (Cancelled)